


UY/URS CORE

| TYPE | FIG. | Dimensions(mm) | | | | | |
|--------------|------|----------------|----------|----------|----------|----------|----------|
| | | A | B | C | D | E | F |
| UY35/12.5/12 | 1 | 35.5±0.5 | 12.5min | 11.9±0.2 | 9.5±0.3 | 21.3±0.2 | 31.3±0.2 |
| UY35/12/12.5 | 1 | 35.0±0.5 | 12.0min | 12.5±0.2 | 10.0±0.3 | 23.2±0.2 | 33.2±0.2 |
| UY35/12.3/13 | 1 | 35.5±0.5 | 12.3min | 13.0±0.2 | 10.0±0.2 | 22.2±0.2 | 32.2±0.2 |
| URS18.5 | 2 | 18.5±0.5 | 11.4±0.2 | 10.0±0.5 | 7.0±0.2 | 7.5±0.5 | 7.4±0.2 |

ET CORE

| TYPE | FIG. | Dimensions(mm) | | | | | |
|---------------|------|----------------|------------|---------|---------|----------|----------|
| | | A | B | C | D | H | M |
| ET20/20/4 | 1 | 20.1±0.5 | 20.1±0.5 | 4.4±0.3 | 3.9±0.3 | 2.0±0.2 | 2.0±0.2 |
| ET20/20/5 | 1 | 20.1±0.5 | 20.1±0.5 | 5.4±0.3 | 4.0±0.2 | 2.0±0.2 | 2.0±0.2 |
| ET23.5/22/3.5 | 1 | 23.5±0.5 | 22.0±0.3 | 3.5±0.2 | 3.8±0.1 | 2.2±0.15 | 2.2±0.15 |
| ET24/24/4 | 1 | 24.2±0.5 | 24.2±0.5 | 4.0±0.3 | 4.0±0.3 | 2.4±0.15 | 2.4±0.15 |
| ET25/25/7 | 1 | 24.6±0.3 | 24.8±0.3 | 7.0±0.2 | 6.9±0.2 | 2.5±0.15 | 2.5±0.15 |
| ET26/26/4.5 | 1 | 26.0±0.4 | 26.0±0.4 | 4.5±0.3 | 4.5±0.3 | 2.5±0.15 | 2.5±0.15 |
| ET28/28/5 | 1 | 28.45±0.55 | 28.45±0.55 | 5.0±0.3 | 5.0±0.3 | 2.9±0.2 | 2.9±0.2 |
| ET29/30/5 | 1 | 29.0±0.3 | 30.0±0.3 | 5.0±0.3 | 5.0±0.3 | 2.9±0.2 | 2.9±0.2 |
| ET35/35/7.5 | 1 | 35.3±0.6 | 35.3±0.6 | 7.5±0.3 | 7.3±0.3 | 4.0±0.2 | 4.0±0.2 |


UY/URS CORE

FIG.1




FIG.2

| S3*S4*h2 | S1*S2*h1 | Cl (mm ³) | Ae (mm ²) | Le (mm) | Ve (mm ³) | AL±25%(nH/N ²) | | Weight g/PRS |
|-------------|-------------|--------------------------|--------------------------|------------|--------------------------|----------------------------|--|-----------------|
| | | | | | | FW40 | | |
| 3.2*2.0*2.0 | 3.0*2.0*2.0 | 1.28 | 111 | 142.4 | 17311 | | | 87.10 |
| 3.0*1.8*2.5 | 2.5*1.8*2.0 | 1.2 | 122 | 147 | 19461 | | | 95.00 |
| 3.2*1.8*2.2 | 3.0*1.8*2.0 | 1.1 | 128 | 151.3 | 19300 | | | 96.20 |
| | | | 38 | 43.5 | | 1500 | | 10.50 |


ET CORE

FIG.1

| Cl (mm ³) | Ae (mm ²) | Le (mm) | Ve (mm ³) | AL±25%(nH/N ²) | | | Weight g/PCS |
|--------------------------|--------------------------|------------|--------------------------|----------------------------|------|-------|-----------------|
| | | | | FW5K | FW7K | FW10K | |
| 2.96 | 17.6 | 52.10 | 917.0 | 2000 | 2700 | 3600 | 4.3 |
| 2.34 | 21.6 | 50.58 | 1092.5 | | | 5500 | 5.5 |
| 5.00 | 13.5 | 66.60 | 899.1 | 1700 | 2000 | 3000 | 4.8 |
| 3.42 | 17.8 | 61.00 | 1090.0 | 2000 | 2700 | 3600 | 6.8 |
| 3.24 | 20.0 | 63.00 | 1400.0 | 2500 | 3000 | 4000 | 13.0 |
| 3.12 | 21.1 | 66.00 | 1395.0 | 2200 | 2800 | 3600 | 6.4 |
| 2.61 | 27.4 | 71.40 | 1950.0 | 2600 | 3600 | 4500 | 11.0 |
| 2.67 | 27.9 | 74.50 | 2070.0 | 2600 | 3600 | 4500 | 11.2 |
| 1.48 | 58.6 | 86.70 | 5080.0 | 4000 | 5000 | 6400 | 27.5 |