



|                   |      |               |
|-------------------|------|---------------|
| CUSTOMER TERMINAL | ROHS | Lead(Pb)-free |
|                   | YES  | YES           |

## 1. Mechanical Dimensions



## 2. Schematic Diagram



## 3. Material List

Core:FW44 EFD25/25/9  
 Bobbin:Fwb2506(5+5PIN)  
 Wire:2UEW TIW  
 Copper foil:0.025t\*6.0mm  
 Operating Temperature: -30 to115 °C

## 4. Electrical Specification

Inductance :  $L(1-2):2.0mH \pm 5\%$  50KHZ , 1.0V  
 Leakage Inductance : 30uH MAX 50KHZ , 1.0V  
 DCR : (1-2)=1.62Ω MAX (8-6)=3.696Ω MAX  
 Hi-Pot:P-S: AC 60Hz 4000V 1mA 3S  
 P-CORE: AC 60Hz 500V 1mA 3S

|      |       |                          |      |                |          |                    |                           |
|------|-------|--------------------------|------|----------------|----------|--------------------|---------------------------|
| REV. | DATE  | <br>Convention Placement | DRW. | Drawing Title: | Part No: |                    |                           |
| 0    | 00/00 |                          | CHK. |                |          | <b>TRANSFORMER</b> | FWPTEFD25H202J-1          |
|      |       |                          | APP. |                |          | Customer P/N       | Specification Sheet 1of 1 |

**ROHS**

[www.ferriwo.com](http://www.ferriwo.com)